

imageRUNNER
C3120

Canon
Delighting You Always

The New imageRUNNER C3120

ELEVATING QUALITY WITH SIMPLICITY

Seamless functionality, maximum performance



Business Can Be Simple

EASY & EFFICIENT

Designed with simplicity in mind, the imageRUNNER C3120 brings even greater workflow productivity and security by streamlining daily operations. With V² colour technology, standard wi-fi and Direct Access Point, enjoy quality colour prints with seamless connection.

V² COLOUR

Canon's V² colour imaging technology delivers outstanding colour quality. Be impressed with vivid and vibrant quality prints time after time.

USABILITY


APPLICATION LIBRARY

Use the application library for better work efficiency. Save time by making frequently performed operations or functions into an application that can be executed with a single button.

- **PRINT TEMPLATE**
Store frequently used form templates with predefined settings.
- **STANDBY SLIDE**
Display customised information on operation panel.
- **CONSUMABLES INFORMATION**
Keep track of toner levels at a glance.
- **SCAN TO PRESET DESTINATION**
Send scanned documents directly to a desired location.
- **ID Cards**
Perform a copy of an ID card on both sides conveniently.




Print Template



Standby Slide




Consumables Information




Scan to Preset Destination



ID Card Copy (Simple)



Copy (BleedReduce)



Copy (Eco)

SIMPLE, INTUITIVE NAVIGATION

Touch panel buttons, allowing home keys customisation and navigation through swipe and flick actions.



MULTIPLE PAPER SUPPORT

iR C3120 supports heavy paper printing. Heavy paper of up to 300gsm can be loaded in the multi-purpose tray. Foolscap/ Folio, India Legal are also supported in Cassette 2, 3, 4 and MPT.



PRODUCTIVITY

Raise productivity with effective finishing accessories and paper handling capabilities.

SMALL SIZE PAPER SUPPORT

Small size originals such as A5 and A6 paper is supported, enabling the use of continuous scanning for small size paper that is high in demand at hotel, shops, medical institutions and regular offices.



SCAN TO EMAIL/FOLDERS

Increase productivity by scanning directly to email or folders. Supported file formats include JPEG, TIFF, compact and searchable PDF.




SMART SCAN

Scanned documents are rotated automatically with OCR, reducing the need for manual correction.



PLATEN COVER

Secure originals in position on the platen glass for scanning.



DUPLEX ADF

Scan double sided effortlessly without manually flipping paper.



INNER FINISHER

Collate, group and staple printouts. Supports ECO staple, staple-on-demand and standard stapling method.



SMART FEATURES

UNIFLOW ONLINE EXPRESS

Track and manage print, copy, scan and fax usage with usage reports. Optimise your prints through reporting and usage analytics.



MOBILE PRINTING

Canon Print Business app and a variety of mobile print service plugins such as, Canon Print Service, Google Cloud Print, AirPrint and Mopria Print Service are supported, enabling users to print from smart devices.



DIRECT CONNECTIVITY WITH MOBILE

The imageRUNNER C3120 comes with Direct Access Point capability. Print directly without requiring to be in the same network.



SPECIFICATIONS

Main Unit		
Machine type	A3 Colour Laser Multifunctional	
Core functions	Print, Copy, Scan, Send and Optional Fax	
Control Panel	5 inch TFT LCD WVGA Colour Touch panel	
Memory	Standard: 2.0GB RAM	
Storage	eMMC Standard: 2.0GB.	
Interface Connection	NETWORK	Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE802.11b/g/n); Optional: NFC
	OTHERS	Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1; Optional: Copy Control Interface
Paper supply capacity (A4, 80gsm)		Standard: 1,200 Sheets 100-sheets Multi-purpose tray, 2 x 550-sheets Paper cassette Maximum: 2,300 Sheets (with Cassette Feeding Unit-AP1)
Paper output capacity (A4, 80gsm)		Standard: 250 Sheets Maximum: 700 Sheets (with Inner Finisher-K1 and Copy Tray J2)
Supported media types	Multi-purpose Tray:	Thin, Plain, Heavy*, Recycled, Coated*, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Envelope * SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper.
	Paper Cassette 1/2:	Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelope* * Lower Cassette: Envelope Feeder Attachment A is required.
Supported media sizes	Multi-purpose Tray:	Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Foolscap, India Legal ,SRA3 Envelope [COM10 No.10, Monarch,ISO-C5, DL] Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm
	Paper Cassette 1:	Standard size: A4, A5, A5R, A6R, B5 Custom size: 105.0 x 148.0 mm up to 297.0 x 215.9 mm Envelope: ISO-C5
	Paper Cassette 2:	Standard size: A3, A4, A4R, A5,A5R, A6R, B4, B5, B5R, Foolscap, India Legal Custom size: 105.0 x 148.0 mm up to 304.8 x 457.2 mm Envelope: [COM10 No.10, Monarch, DL]* * Envelope Feeder Attachment A is required.
Supported media weights	Multi-purpose Tray:	52 to 256gsm* (coated paper), 52 to 300** gsm (heavy paper) * Coated (257 to 300 gsm) requires media adjust kit and service mode setting ** SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm)
	Paper Cassette 1/2	52 to 220 gsm
	Duplex:	52 to 220 gsm
Warm-up Time		From Sleep Mode: 10 Seconds or Less From Power On : 19s or Less* * Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)		565 x 664 x 880 mm
Installation Space(W x D)		1,141 x1,117 mm * with Cassette open
Weight		Approx. 60.1kg without toner
Print specifications		
Print Speed (BW/CL)		Up to 20/20 ppm (A4, A5, A5R, A6R), Up to 15/15 ppm (A3)
Print Resolution (dpi)		600 x 600, 1200 x 1200 (half-speed)
Page description languages		Standard: UFR II Optional: PCL6, Adobe®PostScript®3™
Direct Print		Supported file types: PDF, EPS, TIFF/JPEG, XPS* * XPS is supported from LPR command print only.
Fonts		PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Barcode fonts* PS fonts: 136 Roman * Barcode Printing Kit-D1 is required
Operating System		UFR II: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/ Server2016/Server2019, Mac OS X(10.10 or later) PCL: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/ Server2016/Server2019 PS: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/ Server2016/Server2019, Mac OS X (10.10 or later) PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)
Copy Specifications		
Copy Speed (BW/CL)		Up to 20/20 ppm (A4, A5, A5R, A6R), Up to 15/15 ppm (A3)
First-Copy-Out Time (A4) (BW/CL)		Approx. 5.9 / 8.2 seconds or less
Copy resolution (dpi)		600 x 600
Multiple Copies		Up to 999 copies
Copy Density		Automatic or Manual (9 Levels)
Magnification		Variable zoom: 25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%
Scan Specifications		
Type		Optional: Colour Platen or Duplexing Automatic Document Feeder (DADF)
Document Feeder Paper Capacity (80 gsm)		100 Sheets
Acceptable originals and weights		Platen: Sheet, Book, and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)
Supported media sizes		Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7mm to 297.0 x 431.8mm
Scan Speed (ipm: BW/CL; A4)		1-sided Scanning: 55/55 (300 x 300 dpi, send), 30/30 (600 x 600 dpi, copy) 2-sided Scanning: 27.5/27.5 (300 x 300 dpi, send), 15/15 (600 x 600 dpi, copy)

Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Fax: up to 600 x 600
Pull Scan Specifications	ScanGear MF. For both TWAIN and WIA Supported OS: Windows® 7/8.1/10
Scan Method	PushScan, PullScan, Scan to Network, Scan to memory media (USB Memory Key), Scan to cloud-based services(uniFLOW)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP Optional: Super G3 FAX
Address Book	LDAP (50)/Local (300)/One-touch(281)
Send resolution (dpi)	Push: 300 x 300 (Email/SMB/FTP), 192 x 204 (iFAX) Pull: 50 x 50, 75 x 75, 150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600
Communication protocol	FTP (TCP/IP), SMB (TCP/IP), SMTP
File Format	Standard: TIFF, JPEG™ , PDF(Compact, Searchable, Encrypted, Digital Signature) *1 <i>Single Page Only</i>
Fax Specifications	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine/Photo), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5*2, A5R*2, B4, B5*1, B5R*2 Receiving: A3, A4, A4R, A5R, B4, B5, B5R *1 Sent as B4 *2 Sent as A4
FAX memory	Up to 512 pages
Speed dials	Max. 281
Group dials/destinations	Max. 299 dials
Sequential broadcast	Max. 310 addresses
Memory backup	Yes
Environmental Specifications	
Power source	220-240V 50/60Hz 10A
Power consumption	Maximum: Approx. 1500W or less Standby: Approx. 34.3W*1 Sleep mode: Approx. 2W*2 , Approx. 1W*3 *1 Reference value: measured one unit *2 Wireless LAN power save mode OFF *3 Wireless LAN power save mode ON *2-*3 Sleep mode is not available in all circumstances due to certain settings.

Consumables	
Toner Yield (Estimated @ 5% Coverage)	NPG-67 TONER BK: 36,000 pages NPG-67 TONER C/M/Y: 19,000 pages

Paper Supply Options		
Cassette Feeding Unit-AP1	Paper Capacity:	550 sheets x 2 (80 gsm)
	Paper Type:	Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched
	Paper Size:	A3, A4, A4R, A5, A5R, A6R, B4, B5 ,B5R,
	Custom Size:	105.0 x 148 mm to 304.8 x 457.2 mm
	Paper Weight:	52 to 220 gsm
	Power Supply:	From the Main Unit
	Dimensions (W x D x H):	565 x 615 x 248 mm
	Weight:	Approx. 16 kg

Output options	
Inner Finisher-K1	Tray Capacity (with 80gsm paper):
	Number of Trays: 2
	Lower Tray1: A4, A5, A5R, B5: up to 500 sheets SRA3, A3, A4R, B4, B5R: up to 250 sheets A6R: up to 30 sheets
	Upper Tray2: A4, A5, A5R, B5: up to 100 sheets SRA3, A3, A4R, A6R, B4, B5R: up to 50 sheets
	Paper Weight:
	Lower Tray1: 52 to 256 gsm
	Upper Tray2: 52 to 300 gsm
	Staple Position: Corner, Double
	Staple Capacity: A4/B5: 50 sheets (52 to 90 gsm) A3/B4/A4R: 30 Sheets (52 to 90 gsm)
	Eco Staple: A4: 4 Sheets (54 to 81.4gsm)
	Staple On Demand: Approx. 40 sheets (80 gsm)
	Power Supply: From the main unit
	Dimensions (W x D x H): 634 mm x 525 mm x 188 mm (when the extension tray and rotary tray are extended)
Weight: Approx. 8 kg	

Hardware Accessories	
PLATEN COVER-Y2, DADF-BA1,INNER 2WAY TRAY-J1, COPY TRAY-J2, MAIN BODY HTR-A, READER HEATER-L3, IC Card Reader Attachment-B2,COPY CARD READER-F1 , COPY CARD READER ATTACHMENT-H3, UTILITY TRAY-B1 ,3 Way Unit-D1, PS Printer Kit-CA1, PCL Printer Kit-CA1,BARCODE PRINTING KIT-D1 , COPY CONTROL INTERFACE KIT-D1, NFC KIT-D1 , SUPER G3 FAX BOARD-AV3, ADF ACCESS HANDLE-A1, STAPLE-P1	



Delighting You Always

SOUTH & SOUTHEAST ASIAREGIONAL HEADQUARTERS
CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #15-10 Galaxis, Singapore 138522
Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP